


Data sheet

valid from: 3/31/20



Tank adaptor adjustable PVC-U Union with spigot/reducing socket metric

Model:

- Gasket: flat gasket EPDM
- Washer: PP
- Spare parts on request

d (mm)	d1 (mm)	Code	SP	Weight (kg)
20	25	161 050 206	0	0.046
25	32	161 050 207	50	0.066
32	40	161 050 208	50	0.106
40	50	161 050 209	35	0.190
50	63	161 050 210	25	0.248
63	75	161 050 211	15	0.352
75	90	161 050 212	20	0.539
90	110	161 050 213	10	1.083
110	125	161 050 214	6	1.350

d (mm)	L3 max (mm)	Diameter of bore in tank side (mm)	G (inch)	L1 (mm)	L2 (mm)	L (mm)	L4 (mm)	s (mm)	M
20	23	28	¾	13	19	42	16	32	
25	23	35	1	15	22	45	19	40	
32	24	43	1 ¼	17	26	49	22	50	
40	21	55	1 ½	19	31	48	26	60	
50	21	61	2	21	38	52	31	69	
63	23	77	2 ½	23	44	53	38	85	
75	20	89	3	26	51	56	44	100	
90	20	115		32	61	62	51	125	M113
110	22	135		36	69	66	61	147	M133

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>