Data sheet

valid from: 6/30/17





Rotary Peeler RS

This innovative Rotary Peeler RS is designed for universal peeling at the pipe end for electrofusion couplings, tees and elbows and as well as for electrofusion saddles. Suitable for peeling PE80, PE100, PEX and PP pipes.

Features and your advantage:

Spring loaded peeling blade: Peeling quality independent of pipe ovality or tolerances Pivoted mounted peeling blade: To compensate the shape of coiled pipe Optimized cutting geometry: Defined chip thickness with cutting width overlap One tool per dimension: Minimized swivel radius for peeling in narrow locations Peeling length: No limitation of peeling length

Guidance rolls:3-point-support for dimensional optimized cutting feed

Time saving:Tool is always ready for use, it can be used for the next peeling without having to set the peeling blade back in its origin position

Your advantage: Time saving and highest repeatable peeling quality at smallest rotation radius. No operator errors possible when changing dimension

Included:1 x Rotary Peeler RS, Transport case, Operating manual, Spare parts list

d	Article	Code	SP	Weight
(mm)				(kg)
40	RS 40	790 136 001	1	1.310
50	RS 50	790 136 002	1	1.310
63	RS 63	790 136 003	1	1.310
75	RS 75	790 136 004	1	1.540
90	RS 90	790 136 005	1	1.540
110	RS 110	790 136 006	1	1.540
125	RS 125	790 136 007	1	1.730
140	RS 140	790 136 008	1	1.730
160	RS 160	790 136 009	1	1.730
180	RS 180	790 136 010	1	2.030
200	RS 200	790 136 011	1	2.030
225	RS 225	790 136 012	1	2.030
250	RS 250	790 136 013	1	2.440
280	RS 280	790 136 014	1	2.440
315	RS 315	790 136 015	1	2.440

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com